


SIPMOS® Power Transistor

BUZ 30 A

- N channel
- Enhancement mode
- Avalanche-rated



Type	V_{DS}	I_D	$R_{DS\ (on)}$	Package ¹⁾	Ordering Code
BUZ 30 A	200 V	21 A	0.13 Ω	TO-220 AB	C67078-S1303-A3

Maximum Ratings

Parameter	Symbol	Values	Unit
Continuous drain current, $T_C = 26^\circ\text{C}$	I_D	21	A
Pulsed drain current, $T_C = 25^\circ\text{C}$	$I_{D\ puls}$	84	
Avalanche current, limited by $T_{j\ max}$	I_{AR}	21	
Avalanche energy, periodic limited by $T_{j\ (max)}$	E_{AR}	12	mJ
Avalanche energy, single pulse $I_D = 21\text{ A}$, $V_{DD} = 50\text{ V}$, $R_{GS} = 25\text{ Ω}$ $L = 1.53\text{ mH}$, $T_j = 25^\circ\text{C}$	E_{AS}	450	
Gate-source voltage	V_{GS}	± 20	V
Power dissipation, $T_C = 25^\circ\text{C}$	P_{tot}	125	W
Operating and storage temperature range	T_j , T_{stg}	- 55 ... + 150	°C

Thermal resistance, chip-case	$R_{th\ JC}$	≤ 1.0	K/W
DIN humidity category, DIN 40 040		E	-
IEC climatic category, DIN IEC 68-1		55/150/56	

1) See chapter Package Outlines.

Electrical Characteristicsat $T_j = 25^\circ\text{C}$, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	

Static characteristics

Drain-source breakdown voltage $V_{GS} = 0 \text{ V}, I_D = 0.25 \text{ mA}$	$V_{(BR) DSS}$	200	—	—	V
Gate threshold voltage $V_{GS} = V_{DS}, I_D = 1 \text{ mA}$	$V_{GS (\text{th})}$	2.1	3.0	4.0	
Zero gate voltage drain current $V_{DS} = 200 \text{ V}, V_{GS} = 0 \text{ V}$ $T_j = 25^\circ\text{C}$ $T_j = 125^\circ\text{C}$	I_{DSS}	—	0.1	1.0	μA
—	—	—	10	100	
Gate-source leakage current $V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$	I_{GSS}	—	10	100	nA
Drain-source on-resistance $V_{GS} = 10 \text{ V}, I_D = 13.5 \text{ A}$	$R_{DS (\text{on})}$	—	0.10	0.13	Ω

Dynamic characteristics

Forward transconductance $V_{DS} \geq 2 \times I_D \times R_{DS(\text{on})\text{max}}, I_D = 13.5 \text{ A}$	g_{fs}	6	15	—	S
Input capacitance $V_{GS} = 0 \text{ V}, V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$	C_{iss}	—	1400	1900	pF
Output capacitance $V_{GS} = 0 \text{ V}, V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$	C_{oss}	—	280	400	
Reverse transfer capacitance $V_{GS} = 0 \text{ V}, V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$	C_{rss}	—	130	200	
Turn-on time t_{on} , ($t_{on} = t_{d(on)} + t_r$) $V_{DD} = 30 \text{ V}, V_{GS} = 10 \text{ V}, I_D = 3 \text{ A}, R_{GS} = 50 \Omega$	$t_{d(on)}$	—	30	45	ns
	t_r	—	70	110	
Turn-off time t_{off} , ($t_{off} = t_{d(off)} + t_f$) $V_{DD} = 30 \text{ V}, V_{GS} = 10 \text{ V}, I_D = 3 \text{ A}, R_{GS} = 50 \Omega$	$t_{d(off)}$	—	250	320	
	t_f	—	90	120	

Electrical Characteristics (cont'd)
at $T_j = 25^\circ\text{C}$, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	


Reverse diode

Continuous reverse drain current $T_C = 25^\circ\text{C}$	I_S	—	—	21	A
Pulsed reverse drain current $T_C = 25^\circ\text{C}$	I_{SM}	—	—	84	
Diode forward on-voltage $I_S = 42 \text{ A}, V_{GS} = 0 \text{ V}$	V_{SD}	—	1.2	1.6	V
Reverse recovery time $V_R = 10 \text{ V}, I_F = I_S, di_F / dt = 100 \text{ A}/\mu\text{s}$	t_{rr}	—	180	—	ns
Reverse recovery charge $V_R = 10 \text{ V}, I_F = I_S, di_F / dt = 100 \text{ A}/\mu\text{s}$	Q_{rr}	—	1.2	—	μC

Characteristics at $T_j = 25^\circ\text{C}$, unless otherwise specified.

Total power dissipation


$$P_{\text{tot}} = f(T_c)$$



Safe operating area

$$I_D = f(V_{DS})$$


parameter: $D = 0.01, T_c = 25^\circ\text{C}$



Typ. output characteristics

$$I_D = f(V_{DS})$$


parameter: $t_p = 80 \mu\text{s}$



Typ. transfer characteristics


$$I_D = f(V_{GS})$$

parameter: $t_p = 80 \mu\text{s}, V_{DS} = 25 \text{ V}$




Typ. drain-source on-resistance

$R_{DS(on)} = f(I_D)$
parameter: V_{GS}




Drain-source on-resistance

$R_{DS(on)} = f(T_j)$
parameter: $I_D = 13.5 \text{ A}$, $V_{GS} = 10 \text{ V}$, (spread)




Typ. forward transconductance

$g_{fs} = f(I_D)$
parameter: $t_p = 80 \mu\text{s}$



Gate threshold voltage


$V_{GS(th)} = f(T_j)$
parameter: $V_{GS} = V_{DS}$, $I_D = 1 \text{ mA}$, (spread)



Typ. capacitances

$$C = f(V_{DS})$$


parameter: $V_{GS} = 0 \text{ V}$, $f = 1 \text{ MHz}$



Drain current

$$I_D = f(T_C)$$


parameter: $V_{GS} \geq 10 \text{ V}$



Forward characteristics of reverse diode

$$I_F = f(V_{SD})$$


parameter: T_j , $t_p = 80 \mu\text{s}$, (spread)



Avalanche energy $E_{AS} = f(T_j)$

parameter: $I_D = 21 \text{ A}$, $V_{DD} = 50 \text{ V}$


$$R_{GS} = 25 \Omega, L = 1.53 \text{ mH}$$



Transient thermal impedance

$$Z_{thJC} = f(t_p)$$

parameter: $D = t_p / T$



Typ. gate charge

$$V_{GS} = f(Q_{Gate})$$

parameter: $I_{D \text{ puls}} = 31.5 \text{ A}$

